



i2c packet

Search

[Advanced Scholar Search](#)
[Scholar Preferences](#)
[Scholar Help](#)
ScholarResults 1 - 10 of about 517 for i2c packet with **Safesearch on**. (0.12 seconds)
[All articles](#) [Recent articles](#)
Personal digital assistant (PDA) based I2C bus analysis

JW Bruce, MA Gray, RF Follett - Consumer Electronics, IEEE Transactions on, 2003 -
 ieeexplore.ieee.org

... I2CLib_Recv(UInt16 refNum, UInt8 *addr, UInt8 *data, UInt8 *len) This function
 receives an entire **I2C packet** from the software read FIFO. ...

[Cited by 4](#) - [Web Search](#) - [BL Direct](#)

System Architecture Directions for Networked Sensors - group of 94 »

J Hill, R Szewczyk, A Woo, S Hollar, D Culler, K ... - portal.acm.org

... 0 AM temperature 78 32 AM light 146 8 AM 356 40 **Packet** 334 40 RADIO byte 810 8 RFM
 310 1 Photo 84 1 Temperature 64 1 UART 196 1 UART **packet** 314 40 **I2C** bus 198 ...

[Cited by 935](#) - [Web Search](#) - [BL Direct](#)

WISENET

D PATNODE, DR SCHERTZ - cegt201.bradley.edu

... The main flow of WiseDB was to wait until a **packet** was ... Initialize Hardware Activate
 Sensors Acquire Sensor Data Format Data **Packet** Transmit Data **Packet** ...

[View as HTML](#) - [Web Search](#)

Shift invariant wavelet packet bases - group of 4 »

I Cohen, S Raz, D Malah - Acoustics, Speech, and Signal Processing, 1995. ICASSP-95., ..., 1995 -
 ieeexplore.ieee.org

... [10] I. Cohen, S. Raz and D. Malah, "Orthonormal shift- invariant wavelet **packet**
 decomposition and represen- tation ... **i2c**) (21) (ln,s (l'-l.Zn+l.,n+li 3t) ig. ...

[Cited by 26](#) - [Web Search](#)

Two-level contention resolution scheme for WDM networks with control channels - group of 2 »

DS Kim, CK Un - Electronics Letters, 1993 - ieeexplore.ieee.org

... Fig. 4 OC-I2c transmitter and receiver traces Receiver ... cycles. The length of a
 data **packet** is equal to that of a cycle (= N minislots). Each ...

[Cited by 1](#) - [Web Search](#) - [BL Direct](#)

Design and implementation of a sensor network node for ubiquitous computing environment - group of 3 »

Y Kawahara, M Minami, H Morikawa, T Aoyama - Vehicular Technology Conference, 2003. VTC
 2003-Fall. 2003 ..., 2003 - ieeexplore.ieee.org

... void to_app_layer(packet_type* **packet**); // send data to application CPU via **I2C**
 void from_app_layer(packet_type* **packet**); // receive data from application CPU ...

[Cited by 8](#) - [Web Search](#) - [BL Direct](#)

PRODUCTS

L **PACKET**, SM DC, DC CONVERTERS - IEEE CIRCUITS & DEVICES MAGAZINE, 2003 -
 ieeexplore.ieee.org

... protection, the SR70 is ideal for use in such high-speed signal interface applications
 as ADSL, USB1.1/2.0 ports, **I2C**.microprocessor buses, video ... **LEGEND PACKET** ...

[Web Search](#)[System Architecture for Networked Sensors - group of 2 »](#)

J Hill, R Szewczyk, A Woo, S Hollar, D Culler, K ... - Architectural Support for Programming Languages and ..., 2000 - cse.unsw.edu.au

... <http://tinyos.millennium.berkeley.edu> Composition into a Complete Application RFM

Radio byte Radio **Packet i2c** Temp photo Messaging Layer clocks bit byte **packet** ...

[Cited by 4](#) - [View as HTML](#) - [Web Search](#)

[THE EMERALD PROTOCOL SUITE: DESIGN AND IMPLEMENTATION OF A MODULAR, DISTRIBUTED](#)

B Palmintier - 2004 - hubbard.engr.scu.edu

... Figure 11: Basic **I2C packet** format. ... 34 xvii Page 18. Figure 14: The Status **Packet**

Structure consists of a single byte enclosed in an **I2C packet**..35 ...

[View as HTML](#) - [Web Search](#)

[Readout of the CMS Pixel Detector. - group of 3 »](#)

D Kotlinski, R Baur, K Gabathuler, R Horisberger, ... - Proc. Electronics for LHC Experiments (Cracow 2000) - cms.web.psi.ch

... A **packet** includes a header and trailer provided by the TBM chip. ... Both chips, the ROC and the TBM will include **I2C** interfaces in order to be able to program ...

[Cited by 3](#) - [View as HTML](#) - [Web Search](#)

Google 

Result Page: [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [Next](#)

[Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2006 Google



i2c rebroadcast

Search

[Advanced Scholar Search](#)
[Scholar Preferences](#)
[Scholar Help](#)
ScholarResults 1 - 6 of 6 for **i2c rebroadcast** with **Safesearch on**. (0.10 seconds)System Architecture Directions for Networked Sensors - group of 94 »

J Hill, R Szewczyk, A Woo, S Hollar, D Culler, K ... - portal.acm.org

... TX RX I2C SPI AT 90LS8535 32.768 MHz clock ... Any sensors in range of this broadcast record the identity of the base station and then **rebroadcast** out the update. ...Cited by 935 - [Web Search](#) - [BL Direct](#)From motes to java stamps: smart sensor network testbeds - group of 4 »

TC Henderson, JC Park, N Smith, R Wright - Intelligent Robots and Systems, 2003.(IROS 2003). ..., 2003 - ieeexplore.ieee.org

... configuration SandR { } implementation (cluster (or **rebroadcast** cluster) ... Other sensor options include Dallas 1-Wire, I2C and SPI devices. ...Cited by 5 - [Web Search](#)ReWINS: a distributed multi-RF sensor control network for industrial automation - group of 2 »

H Ramamurthy, D Lal, BS Prabhu, R Gadh - Wireless Telecommunications Symposium, 2005, 2005 - wireless.ucla.edu

... IEEE 1451) use serial channels like I2C, microwire, field bus for communication and thus in our design the hardware peripherals have been ... **rebroadcast** the packet ...[View as HTML](#) - [Web Search](#)Tangible Toolkits for Reflective Systems Modeling - group of 3 »

TM Gorton - 2003 - timgorton.com

Page 1. Tangible Toolkits for Reflective Systems Modeling by Timothy M. Gorton

Submitted to the Department of Electrical Engineering ...

Cited by 5 - [View as HTML](#) - [Web Search](#) - [Library Search](#)[book] Ambient Intelligence: First European Symposium, Eusai 2003, Veldhoven, the Netherlands, November 3.- ...

E Aarts, R Collier, E Van Loenen - 2003 - books.google.com

... It also provides a wide range of input output interfaces: USB, I2C, PCMCIA, 1 15 Kbits IRDA, ISO 7816-2 Smart- card, 8 bit audio CODEC, graphical LCD ...

[Web Search](#) - [Library Search](#)Report on "DVB-H in China" opportunity study and assessment

D Type, C Workpackages - ist-phenix.org

Page 1. Deliverable 3.1 Report on "DVB-H in China" opportunity study and assessment Deliverable Type * : PU Nature of Deliverable ...

[View as HTML](#) - [Web Search](#)

i2c rebroadcast

Search

[Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2006 Google



eeprom flash i2c

Search

[Advanced Scholar Search](#)[Scholar Preferences](#)[Scholar Help](#)**Scholar**Results 1 - 10 of about 335 for **eeprom****flash** i2c with **Safesearch on**. (0.09 seconds)[All articles](#) [Recent articles](#)8-BIT MCU WITH SINGLE VOLTAGE **FLASH** MEMORY, DATA**EEPROM**, ADC, TIMERS, SPI - group of 16 »

FPS Modes, AH Halt, A Comparator, F gain Op-amp, I ... - us.st.com

... The available memory locations consist of 128 bytes of register locations, 256 bytes of RAM, 128 bytes of data **EEPROM** and up to 4 Kbytes of **flash** program memory ...[View as HTML](#) - [Web Search](#)A 1 GOPS reconfigurable signal processing IC with embedded FPGA and 3-port 1.2 GB/s **flash** memory ...M Borgatti, L Call, G De Sandre, B Foret, D Iezzi, ... - Solid-State Circuits Conference, 2003. Digest of Technical ..., 2003 - [ieeexplore.ieee.org](#)... processing unit tightly connected to a **Flash EEPROM** memory subsystem is ... General Purpose Registers **I2C** Master ... Memory Interface 32 bit External ROM/**FLASH** Port ...[Cited by 1](#) - [Web Search](#)A 32Mb-4b/cell analog **flash** memory supporting variable density with 3V-only supply and serial I/ ...PL Rolandi, M Pasotti, G Campardo, R Canegallo, G ... - Solid-State Circuits Conference, 1999. ESSCIRC'99. ..., 1999 - [ieeexplore.ieee.org](#)... Controller +SPI/**I2C** interface Charge Pumps Redundancy system μ ... The chip is fabricated in a standard 3V 0.5 μ m common-ground NOR **Flash-EEPROM** process (2 polys, ...[Cited by 3](#) - [Web Search](#)Memories: A Survey of Their Secure Uses in Smart Cards - group of 5 »M Neve, E Peeters, D Samyde, JJ Quisquater - Security in Storage Workshop, 2003. SISW'03. Proceedings of ..., 2003 - [ieeexplore.ieee.org](#)... A simple PIC (c Microchip) processor is inserted into the card with an **I2C** access memory (by the same manufacturers as for non ... F. **EEPROM** and **FLASH** With an ...[Cited by 3](#) - [Web Search](#)铁电存储器在单片机系统中的应用 - group of 2 »

吴正民 - 电子产品世界, 2003 - 维普资讯

... ROM技术, 这些只读存储器的数据是不可能修改的。 **EPROM**、 **EEPROM**、 **Flash** 的写入数据都需要很长时间 ... **FM24C04**支持**I2C**串行总线规范 ...[Cited by 1](#) - [Web Search](#)Mikrokontrolery jednoukładowe na podstawie ADuC812 oraz ST52E420I Wykład - [aq.ia.agh.edu.pl](#)... PROTOTYPOWANIE UKŁADÓW ELEKTRONICZNYCH Przykład programowania pamięci **EEPROM** ... **JMP****FLASH** END ... PROTOTYPOWANIE UKŁADÓW ELEKTRONICZNYCH INTERFEJS **I2C** ...[Web Search](#)Sistemas Digitais III (regime nocturno) - group of 3 »ÁC Dpt, R da Disciplina, C Docente, D Co- ... - [est.ips.pt](#)

... Page 2. 3. Programa Memórias **EPROM**, **EEPROM**, **FLASH**, NV-RAM Interface Série-Paralelo ...
Comunicação RS-232, RS-485, IEEE1284, **I2C**, SPI, USB Lógica Programável ...
[View as HTML](#) - [Web Search](#)

[A 64-min single-chip voice recorder/player using embedded 4-b/cell **flash** memory - group of 4 »](#)

M Borgatti, A Rocchi, M Bisio, M Besana, L Navoni, ... - Solid-State Circuits, IEEE Journal of, 2001 -
ieeexplore.ieee.org

... A master/slave **I2C** interface has been added to the MCU to provide a direct link
to ... in a standard 3-V 0.5-mm common-ground NOR embedded **flash EEPROM** process (two ...
[Cited by 3](#) - [Web Search](#) - [BL Direct](#)

[Z8 Encore!@ **Flash** MCU - group of 2 »](#)

MS Timer - dkc3.digikey.com

... Features: • Program Memory Type: **Flash** • On-Chip Special Features: POR, VBO •
WDT • COMM Interfaces: **I2C**, UART, OCD • Speed (20MHz) • Oper. ...

[View as HTML](#) - [Web Search](#)

[Leveraging Boundary Scan resources for comprehensive cluster testing - group of 4 »](#)

H Ehrenberg, N Muench, GE LLC - Proceedings of Board Test Workshop 2004 - tmsinc.co.kr

... 3.3.2 **EEPROM FLASH** devices and other **EEPROM** (such as serial **EEPROM** based on **I2C**
or SPI protocol) can be programmed via Boundary Scan devices if access is ...

[Cited by 1](#) - [View as HTML](#) - [Web Search](#)

Google

Result Page: [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [Next](#)

i2c rebroadcast

Search

[Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2006 Google